

NLT Polaris/Polaris IS/Polaris Plus

CAP LAMP SPECIFICATIONS COMPARISON



nltinc.com

Polaris Cap Lamp	Light Output (Typ)	Beam Patterns	Run Time	Weight	Charge Time	Charger Configuration	Water & Dust Protection	Approvals
Polaris	7,000 Lux	Standard beam pattern and Low-Light/ Emergency setting	Main LED >14 hours; Low-Light/ Emergency setting >7 days	170g (6oz)	<10 Hours	Single, 4, 10, 24 & 48-unit racks; 120V or 240V models	IP67	-
Polaris IS	7,000 Lux	Standard beam pattern and Low-Light/ Emergency setting	Main LED >14 hours; Low-Light/ Emergency setting >7 days	170g (6oz)	<10 Hours	Single, 4, 10, 24 & 48-unit racks; 120V or 240V models	IP67	Intrinsically Safe approved by ATEX, IECEx & MSHA
Polaris Plus	10,000 Lux; Dynamic Turbo Bright: 15,000 Lux	Dual-Beam technology with 3 beams, Dynamic Turbo Bright and Low-Light/ Emergency setting	Main LED >13 hours; Low-Light/ Emergency setting >7 days	170g (6oz)	<10 Hours	Single, 4, 10, 24 & 48-unit racks; 120V or 240V models	IP67	Intrinsically Safe approvals pending

